


Power Inductors – S93000B Series






BACK-SIDE VIEW





IN	MM
0.440	11.18
0.410	10.41
0.285	7.24
0.230	5.84
0.155	3.94
0.135	3.43
0.025	0.64
0.010	0.25

MIL-STD-981
MIL-PRF-27



SPECIFICATIONS

- **Inductance:** 0.1 mH to 10 mH (Series)
  0.025 mH to 2.5 mH (Parallel)
- **Standard Tolerance:** ±10%
- **Operating Temperature:** -55°C to +125°C
- **Storage Temperature:** -60°C to +130°C
- **Temperature rise (at 90°C):** 35°C
- **Terminal Solderability:** MIL-STD-202, Method 208
- **Inductance measured at** 0.1 Vrms, 10 kHz, 0 DC current
- **Insulation Resistance**: MIL-STD-202, Method 302, 1000 megohms minimum at 100 Vdc
- **Terminal Strength**: MIL-STD-202, Method 211, test condition A, 2 lbs
- **Standard Termination Finish:** Tin-lead
- **Weight:** 35.4 gram, maximum
- **Dielectric Withstanding Voltage:** Method 301 of MIL-STD-202, test voltage 200 Vrms
- **Glass Transition Temperature (T_g):** 165°C
- **Coefficient of Thermal Expansion (CTE):**
  Before T_g 18 ppm/°C
  After T_g 54 ppm/°C

FEATURES

- Transfer Molded Package
- Marking: Laser or Ink
- Leadless device for minimum footprint
- Internal Welded Terminations
- Low EMI Radiation
- Low Thermal Expansion permits mounting on most substrate materials
- Outgassing meets NASA spec SP-R-0022A: TML < 1%
- Tape and Reel Packaging available (additional charge)
  Full Reel Quantity (Small): 200 pieces
  Full Reel Quantity (Large): 650 pieces
- Custom Designs: Other electrical configurations and performance characteristics are available in various sizes and package type


APPLICATIONS

These components meet the requirements of MIL-PRF-27 and MIL-STD-981,Class S or Class B classifications:

- **Class S:** Specifically engineered for critical flight operations and essential ground support missions, as well as any application where safety is critical. These components undergo a stringent quality validation process, which includes both Group A and Group B screening as per the requirements of MIL-STD-981.

- **Class B:** Suited for non-critical flight operations and non-essential ground support missions. The quality assurance process for these components encompasses Group A screening as per the requirements of MIL-STD-981.

PART IDENTIFYING NUMBER



K: Inductance Tolerance
M: ±20% K: ±10% J: ±5%

S: Product Class
S: Class S B: Class B

Power Inductors – S93000B Series

Dash Number	C/A CM P/N	Series			Parallel			Power Rating (mW)
		Inductance (mH)	Rated DC Current (mA)	DC Resistance Max (Ω)	Inductance (mH)	Rated DC Current (mA)	DC Resistance Max (Ω)	
93027-002	S93002	0.100 ±10%	600	.96	0.025 ±10%	1200	.240	250
93027-006	S93006	0.250 ±10%	400	1.98	0.062 ±10%	800	.495	250
93027-010	S93010	0.500 ±10%	300	3.35	0.125 ±10%	600	.838	250
93027-014	S93014	0.750 ±10%	250	5.20	0.187 ±10%	500	1.300	250
93027-018	S93018	1.000 ±10%	200	6.90	0.250 ±10%	400	1.725	250
93027-022	S93022	2.000 ±10%	150	12.20	0.500 ±10%	300	3.050	250
93027-026	S93026	3.000 ±10%	120	18.30	0.750 ±10%	240	4.580	250
93027-030	S93030	5.000 ±10%	90	30.40	1.250 ±10%	180	7.600	250
93027-034	S93034	7.500 ±10%	70	46.00	1.875 ±10%	140	11.500	250
93027-038	S93038	10.000 ±10%	50	61.00	2.500 ±10%	100	15.250	250